

**Please Print!** Survey must be fully completed and dated for order processing. Ship to: Job \_\_\_ or Shop \_\_\_ (check one)

Job Name \_\_\_\_\_

Code in Force (i.e. A17, Title 8, B44) \_\_\_\_\_

Job Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip/Postal Code \_\_\_\_\_ Country \_\_\_\_\_

Car # \_\_\_\_\_ Number of Landings \_\_\_\_\_ Travel \_\_\_\_\_ ft Pit Depth \_\_\_\_\_ ft Car Speed: \_\_\_\_\_ fpm.

Jack Mfg. \_\_\_\_\_ Plunger Wall Thickness \_\_\_\_\_ inches Capacity of Car \_\_\_\_\_ lbs. Car Weight \_\_\_\_\_ lbs.

Original Elevator Installing Company: \_\_\_\_\_ Date of installation \_\_\_\_\_ Mfg.'s Job Number \_\_\_\_\_

Include LifeJacket Information Display Option LJ4050 (additional charge applies): \_\_\_ Yes \_\_\_ No (*Required in Michigan*)

Packing, specify style and size \_\_\_\_\_ **Packing Must be Replaced** Is Controller: \_\_\_ Solid State OR \_\_\_ Relay

Is Pit prone to flooding? Yes \_\_\_ No \_\_\_ - - - - - (if yes, NEMA 3R conduit [liquitite flex] is supplied)

Does elevator have a bottom final limit switch? Yes \_\_\_ No \_\_\_ - - - (if yes, it must open prior to buffer engagement)

Does Cylinder have a tapped bleeder hole in the head? Yes \_\_\_ No \_\_\_ - - - (if no, optional drill and tap is supplied)

Is 120VAC available in controller? Yes \_\_\_ No \_\_\_ - - - - - (if no, 480/240 to 120 transformer is supplied)

How many 'wiring' feet from controller to Cylinder head? \_\_\_ Ft - - - (length of shielded cable sent for set coils and encoder)

Special delivery instructions (e.g., Do you have a forklift to get it off the truck?) \_\_\_\_\_

**Pit Information** Record dimensions to 3 decimal places (i.e. 1.234). **DO NOT USE FRACTIONS**

The plunger diameter (PD) must be *accurately* measured to thousandths of an inch. Using a diameter tape, measure the plunger in at least three (3) places. Record these measurements in the blanks below. Start measurements a foot or so above the packing head.

(PD) 1 \_\_\_\_\_. 2 \_\_\_\_\_. 3 \_\_\_\_\_. 4 \_\_\_\_\_

See diagrams on page 2 for graphic illustration of dimensions. These dimensions must be accurate for proper fit. All dimensions below must be in inches.

(BSD) \_\_\_\_\_" (PH) \_\_\_\_\_" (PW) \_\_\_\_\_" (CD) \_\_\_\_\_" (BN) \_\_\_\_\_"  
*Buffer spring diameter Pedestal Height Pedestal Width Cylinder Diameter Number of Buffer springs*

(RB) \_\_\_\_\_" (BS) \_\_\_\_\_" (SD) \_\_\_\_\_" (BB) \_\_\_\_\_" (CHP) \_\_\_\_\_"

Company \_\_\_\_\_ Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip/Postal Code \_\_\_\_\_

Survey completed by \_\_\_\_\_ Date \_\_\_\_\_

PO # \_\_\_\_\_ Charge # \_\_\_\_\_ Adams Order # \_\_\_\_\_

Phone # \_\_\_\_\_ - \_\_\_\_\_ Fax # \_\_\_\_\_ - \_\_\_\_\_ Serial # \_\_\_\_\_